

**RP-GS2024I | 20 Port SFP + 4 Port RJ45/SFP Combo L2+ Managed Switch**

Fiber optik ağlarda merkez ethernet ağ anahtarı olarak kullanılır. Cihaz üzerinde 20 port SFP yuvası ve 4 Port RJ45/SFP combo olmak üzere toplam 24 Port bulunur. GBIC yuvaları 100/1000 GBIC'leri destekler. SNMP , Telnet ve HTTP arayüzleri ile uzaktan erişilebilir. 802.1Q VLAN, 802.1x Security, Rate Control, Port Configuration, Port Mirroring, Port Statistics, QoS gibi L2 yönetim fonksiyonlarını destekler.



- 20 * SFP portu, 100Base FX yada 1000Base-X
- 4* RJ45/SFP(100/1G) portu , auto-detect RJ45/SFP bağlantı
- IPv6 Yönetim
- IPv4 Static Routing
- 8 priority queues are supported on each port for QoS application
- Port-based VLAN, 802.1Q VLAN, Voice VLAN and Q-in-Q(double tagging) function
- Protected Port and LoopBack Detection function
- IEEE 802.1x security function, and VLAN assignment, Guest VLAN functions
- Static Mac address access limit and Dynamic Mac address number on port
- IEEE802.1d & 802.1w & 802.1s
- IP Multicast with IGMP snooping / query / fast leave / filtering /group limited /MVR
- DHCP Client / DHCP Option 82 Relay / DHCP Snooping function
- ACL function for L2 ~ L4 packet control, Ingress/Egress rate control on port
- Broadcast/Multicast/Unicast storm control
- ARP inspection / IP source guard
- RMON 1,2,3,9
- SFP Transceiver DDMI function
- Remote port configuration setting and statistics monitoring
- CPU 416MHz MIPS 24KEc CPU as the main processor which integrated on switch controller
- Memory Flash : SPI 16M Bytes RAM:DDR2 128M Bytes
- Packet Buffer 512K Bytes
- Mac Table Size - 8K & Max Packet Size 9600 Bytes
- Switch capacity 48Gbps

İngilizce döküman için : <http://www.telkolinK.com/downloads/RP-GS2024I.pdf>

24 PORT SFP**100Base-FX****1000Base-X****L2+ Yönetim**