

ECS5510-48S

High Density 48-Port 10G Ethernet L2 Switch



Product Overview

The Edge-Core ECS5510-48S is a 48-port 10 Gigabit Ethernet Layer 2 switch designed from the ground up to be deployed in medium to large data centers. With its unmatched port density, the ECS5510-48S is ideally suited for converged Ethernet applications such as 10 Gigabit Ethernet traffic aggregation and Fibre Channel over Ethernet (FCoE) storage interconnection.

Key Features and Benefits

Performance

The ECS5510-48S is a high density Layer 2 10G Ethernet switch encased in a small 1U form factor. Featuring 48 10G SFP+ interfaces, it offers unparalleled switching capacity, making it the ideal solution for medium to large-sized data centers.

The ECS5510-48S is capable of 960 Gbps of network throughput, enabling the switch to fully support the demand for bandwidth brought on by server virtualization.

Continuous Availability

Dual hot-swappable power supplies enable the system to continue operation even in the event of a single power supply failure. To ensure longevity, the ECS5510-48S employs data center-friendly front to back cooling, dissipating unwanted heat efficiently and effectively.

Data Center Requirements

With Ethernet fast becoming the de facto standard for the interconnection of data center devices, the ECS5510-48S is designed to overcome the challenges of a high-traffic-load environment, ensuring that traffic flows smoothly through the network without delay. It features:

- Jumbo frames up to 10K bytes
- 802.1Qau Quantized Congestion Notification (QCN)
- 802.1Qbb Priority Flow Control (PFC)
- 802.1Qaz Enhanced Transmission Selection (ETS)
- FCoE ACL and FIP snooping

Energy Efficiency

The ECS5510-48S is easy on the environment as well as your energy budget. At less than 3 Watts per port, it is simply without peer. This level of performance is the result of an uncompromising design philosophy, utilizing:

- State-of-the-art packet processor
- Power supplies with greater than 90% efficiency
- Variable speed fans
- Advanced physical layer design

Simple and Flexible Management

The ECS5510-48S features both a user-friendly web interface and a command line interface for the advanced user. SNMP-based management is also fully supported.

Ethernet Switch



Features

Physical Ports

- 48 10 Gigabit SFP+ ports
- 1 RJ-45 management port
- 1 RJ-45 console port
- 2 PSU slots for removable power supplies

Performance

- Switching Capability: 960 Gbps
- Forwarding Rate: 714 Mpps
- Packet Buffer Size: 4 MB
- MAC Address Table: 32K

L2 Features

- Auto-negotiation for port speed and duplex mode
- Flow Control:
 - IEEE 802.3x for full-duplex mode
 - Back-Pressure for half-duplex mode
- Spanning Tree Protocol:
 - IEEE 802.1D Spanning Tree Protocol (STP)
 - IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)
 - IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
 - Per-VLAN Rapid Spanning Tree (PVRST)
- VLANs support:
 - Supports 512 active VLANs
 - Supports IEEE 802.1Q VLANs
 - Port-based VLANs
 - MAC based VLANs
 - Protocol-based VLANs
 - Supports private VLAN edge
 - GVRP
 - QinQ
 - Support IGMP
 - IGMP snooping v1/v2/v3
 - IGMP querier
 - IGMP immediate leave
 - IGMP throttling
 - IGMP filtering
 - IFMPSNP leave proxy
- Supports Multicast VLAN Registration (MVR)
- Provides Link Aggregation
- Support IEEE 802.3ad
- Static trunking

QoS Features

- 8 priority queues per port / 128 groups per system
- Priority queue scheduling scheme: strict priority, WRR
- L2/L3/L4 Traffic classification / Priority Management
 - IEEE 802.1p (CoS)
 - DSCP/ToS
 - TCP/UDP port number
- Per-port bandwidth management

Data Center Features

- FCoE
- ACL and FIP snooping
- 802.1Qau Quantized Congestion Notification (QCN)
- 802.1Qaz Enhanced Transmission Selection (ETS)
- 802.1Qbb Priority Based Flow Control (PFC)

Security

- Supports L2/L3/L4 Access Control Lists
- User/Password-protected system management terminal (SNMP, Telnet, Web)
- Static port security (MAC based)
- Dynamic port security (MAC based)*
- Supports RADIUS authentication
- Supports TACACS+ authentication
- MAC-based authentication
 - User name and password authentication
 - Local authentication
- Remote authentication via RADIUS/TACACS+
- Supports management interface access filtering
 - SNMP
 - Web
 - Telnet
- Supports SSH v1.5/v2
- Supports HTTPS/SSL
- Supports IEEE 802.1X
 - Port-based
 - MAC-based security*

Management

- Switch Management:
 - CLI via console port or Telnet
 - Web management
 - SNMP v1, v2c, v3
- Firmware and Configuration:
 - Firmware upgrade via TFTP server
 - Dual firmware images
 - Multiple configuration files
- Configuration file upload/download via TFTP server
- Supports RMON (group 1,2,3 and 9)
- Supports BOOTP, DHCP for IP address assignment
- Supports SNTp
- Event/Error Log/Syslog
- (Optional) ECView Pro, powerful network management software that maximizes the management capabilities of Edge-Core devices with:
 - Topology management
 - Event management
 - SNMP management

Safety

- CSA (CSA 22.2 NO 60950-1 & UL 60950-1)
- CB(IEC/EN60950-1)

Mechanical

- Dimensions (W x D x H): 440 mm x 596 mm x 44 mm (17.32 x 27.46 x 1.75 inches)
- Weight: 10 kg (22 lbs)
- LED Indicators: Port, Uplink, System, Diagnostic

Electromagnetic Compatibility

- CE Mark
- FCC Class A

Environmental Specifications

- Temperature:
 - 0°C to 40°C (Standard Operating)
 - -40°C to 70°C (Non-operating)
- Humidity: 5% to 95% (Non-condensing)
- Vibration: IEC 68-2-36, IEC 68-2-6
- Shock: IEC 68-2-29
- Drop: IEC 68-2-32

Ordering Information

Optional Accessories

- 10G SFP+ SR
- 10G SFP+ LR
- 10G SFP+ LRM
- 10G SFP+ CR pre-terminated twinax copper cables
- 1G SFPs for 1000BASE-X or 1000BASE-T

Product Description

- 10 Gbps, Small Form Factor Pluggable (Distance: 350 m; Wavelength: 850 nm)
- 10 Gbps, Small Form Factor Pluggable (Distance: 10 km; Wavelength: 1310 nm)

* Future Release

Address : Perpa Ticaret Merkezi, A Blok No.516 Şişli/İstanbul | Tel : +90 212 3204030 | Fax : +90212 3200255 | e-mail : info@telkolink.com

www.telkolink.com

© 2009 telcolink Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000175 Rev. C

