



RS485 Data hatlarını korur. Geniş sıcaklık aralığında çalışır. Güç gerektirmez

Product Description

Features

1. Three stages of protection on every data line
2. Protected signal ground connection
3. Easy to install, plug-and-play
4. 4500V surge protection

Specification

Standard: Accord EIA RS-485 standard
RS485 signal: IEC6100-4-5 and ITU-TK20&21
Working voltage: 0-5V

Limit voltage: <15V

Apply Band rate: 1Mbps

Isolate signal: TXD, RXD, GND

Connector: Standard industrial terminal block

Insert consumption: <0.5dB

Delay time: <1ns

Environment

Working temperature: -20 to 60° C

Storage temperature: -25 to 85° C

Humidity: Relative humidity 5% to 95%

Power

Input powered: No power supply needed

Consumption: No consumption

Dimension

L× W× H: 80mm× 25mm× 22mm

Shell: Alnico

Color: Blue

Weight: 10g

Warranty: 5 years

Approvals: FCC, CE, RoHS approvals

Address : Perpa Ticaret Merkezi, A Blok No.516 Şişli/İstanbul | Tel : +90 212 3204030 | Fax : +90212 3200255 | e-mail : info@telkolink.com

www.telkolink.com

© 2009 telkolink Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000175 Rev. C

Haberleşme sistemlerinde **yüksek performansı** yakalayın

