

OPM-1x/2x Series Optical Power Meter



- ◆ Applicable on singlemode/multimode fibers
- ◆ Microprocessor & linear amplifier ensure long-time accuracy
- ◆ Quick response, no warm-up
- ◆ Interchangeable connectors: FC/SC/ST
- ◆ Dual-way power supply: 9V alkaline battery/AC adapter
- ◆ Pocketsize, lightweight and damp-dust-shock proof
- ◆ Power saving: Auto-off setting
- ◆ MOD tones detection
- ◆ Display Units: dB/dBm/mW
- ◆ PC software for data upload and reporting (OPM-2x only)
- ◆ CE, FCC Certificates



OPM-1x/2x series Optical Power Meter paired with ShinewayTech SLS series Stabilized Laser Source can meet general test requirements of fiber identification, attenuation/loss measurements, continuity verification and transmission quality evaluation on singlemode and multimode fibers in LAN/WAN/CATV infrastructure. OPM-1x/2x is ideal for both lab and field applications offering high quality, high stability and competitive low costs.

Specifications

Model	OPM-15		OPM-25		
	A	B	A	B	C
Calibrated Wavelength ⁽¹⁾	850,1300,1310,1490,1550nm		850,1300,1310,1490,1550,1625nm		
Power Range (dBm) ⁽²⁾	-70~+10	-50~+27	-70~+10	-50~+27	-55~+17
Application Range	Single/Multimode fibers				
Detector Type	InGaAs				
Accuracy	±0.25 dB (5%) @25°C & -10dBm (±0.5 dB@850nm)				
Resolution	0.01dB				
MOD Identification	270,1K,2K Hz				
Display Unit	W/mW/dBm/dB (REF)				
Connector ⁽³⁾	FC (Interchangeable SC, ST)				
Data Storage	N/A		3000 records		
Connectivity	N/A		RS-232		
Power Supply	9V Alkaline Battery(450mAh) / Optional 9V AC Adapter				
Battery Life	≥40hours				
Power Saving	Auto off after 5 minutes idle				

Address : Perpa Ticaret Merkezi, A Blok No.516 Şişli/İstanbul | Tel : +90 212 3204030 | Fax : +90212 3200255 | e-mail : info@telkolink.com

www.telkolink.com

© 2009 telcolink Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000175 Rev. C



Operating Temperature	0°C ~ 50°C (32 ~ 122 F)
Storage Temperature	-20°C ~ 70°C (-4 ~ 158 F)
Relative Humidity	0 ~ 95% (Non-condensing)
Weight	300g (0.66lbs)
Dimensions (H×W×T)	145×75×25mm (5.7×2.9×1inch)

- Note:** (1) Other wavelengths and power ranges are open for customization;
 (2) For Model A at 850nm, the lower limit of measurement range is -60 dBm;
 (3) OPM models with $\Phi 1000\mu\text{m}$ detector are available with:
 FC/SC/ST/DIN/E2000/LC/Universal 1.25mm/Universal 2.5mm connectors.

* Specifications subject to change without notice

Ordering Information

Standard Package:

Instrument, 9V Alkaline battery, Rubber boot, OPM data analysis software CD (for OPM-25), Warranty card, CE certificate, Certificate of calibration, User manual.

Optional Parts

Part Description	Part Number (P/N)	Part Description	Part Number (P/N)
3M Optical patch cord	AC-FJC-03-FC/FC	50M Optical patch cord	AC-FJC-50-FC/FC
SC connector for PM	AC-CONN-SC-P-300	AC adapter for US	AC-ADPT-10-US
ST connector for PM	AC-CONN-ST-P-300	Compact carrying softbag	AC-PB-10

Address : Perpa Ticaret Merkezi, A Blok No.516 Şişli/İstanbul | Tel : +90 212 3204030 | Fax : +90212 3200255 | e-mail : info@telkolink.com

www.telkolink.com

© 2009 telkolink Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000175 Rev. C

Quality Link Connections

