

OPM-50 Intelligent Optical Power Meter

Features

- ◆ Automatic Wavelength Identification
- ◆ Remote Reference Value Setting
- ◆ FTTx Applicable
- ◆ Internal Clock & Fiber S/N Editable
- ◆ Memory of 1000 Test Records
- ◆ Data Transfer to PC via USB
- ◆ USB Power Charging
- ◆ No Warm-up, Quick Start
- ◆ Backlight
- ◆ 125 Hours Continuous Operation
- ◆ Pocketsize, Lightweight and Easy-to-use
- ◆ CE FCC Certificates



OPM-50 paired with SLS-50 Intelligent Stabilized Laser Source can be used to identify fiber, measure attenuation and loss, verify continuity and evaluate fiber link transmission quality.

➤ Automatic Wavelength Identification

Compatible with the digital encryption protocols of SLS-50, OPM-50 can automatically identify the wavelength of the optical signals transmitted from SLS-50 and switch to the corresponding test mode, which greatly reduces the workload at both ends and risk of potential error.

➤ Remote Reference Value Setting

OPM-50 can receive the power parameters of digital-encrypted signal transmitted from SLS-50 as reference for precise link loss measurement even the two units are far apart.

➤ Internal Clock & Fiber S/N Editable

Internal clock enables OPM-50 to save test data with time and editable fiber SN information.

➤ Compatible With FTTx Test

OPM-50 can be applied to measure Triple-play signals (1310nm, 1490nm and 1550nm) on Passive Optical Network (PON).

Specifications

Model	OPM-50	
	A	B
Calibrated Wavelength	850,1300,1310,1490,1550,1625nm	
Application Range	Singlemode/Multimode optical fibers	
Power Range (dBm)	-70 ~ +10	-50 ~ +27
Accuracy	±0.25 dB (5%) @25°C & -10dBm (±0.5 dB@850nm)	
Resolution (dB)	0.01	
MOD Identification	270,1K,2K Hz	
Auto Wavelength Identification	Yes (With SLS-50)	
Display Unit	W/mW/dBm/dB(REF)	
Data Storage	1000 records	
Connectivity	USB	
Power Saving	Auto-off after 5 minutes idle	
Detector Type	InGaAs	
Connector	FC (Interchangeable SC/ST)	
Power Supply	Lithium Battery/ AC Adapter	
Battery Life	Continuous operation ≥125 hours; Standby ≥250hours	
Weight	315g (0.69 lbs)	
Dimensions (H × W × T)	177×80×44mm (6.97×3.15×1.73 inch)	

Note: OPM models with $\Phi 1000\mu\text{m}$ detector are available with:
FC/SC/ST/DIN/E2000/LC/Universal 1.25mm/Universal 2.5mm connectors.

* Specifications subject to change without notice

Ordering Information

Standard Configuration:

Instrument, Lithium battery, AC adapter, USB cable, OPM data analysis software CD, Soft carrying case, Warranty card, CE certificate, Certificate of Calibration, User's manual.

Optional Parts

Part Description	Parts Number (P/N)	Part Description	Parts Number (P/N)
3-meter Optical Fiber	AC-FJC-03-FC/FC	ST OPM Connector	AC-CONN-ST-P-300
SC OPM Connector	AC-CONN-SC-P-300		

Address : Perpa Ticaret Merkezi, A Blok No.516 Şişli/İstanbul | Tel : +90 212 3204030 | Fax : +90212 3200255 | e-mail : info@telkolink.com

www.telkolink.com

© 2009 telcolink Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000175 Rev. C

