

OVA-50 Optical Variable Attenuator



Features

- ◆ Attenuation Range: 2.5-60dB
- ◆ Direct Output Power Control
- ◆ Working modes:
 - Output power control
 - Absolute/relative attenuation setting
 - Program (Preprogramming frequently-used attenuations)
- ◆ Adjust at step of 0.05/0.10/1.00/10.00 dB
- ◆ PC Control via USB
- ◆ Backlight
- ◆ Over 30 Hours Continuous Operation
- ◆ Handheld, Light and Easy-to-use
- ◆ CE FCC Certificates



OVA-50 Optical Variable Attenuator can precisely attenuate input optical signals at 1310/1490/1550/1625nm wavelengths and directly output defined stabilized optical signals. OVA-50 is applicable in various testing situations:

- Network/BER testing
- Power meter calibration
- Link loss simulation
- Optical margin analysis

➤ Direct Output Power Control

Normal attenuator can only introduce and display an attenuation value, you need a separate power meter to measure or adjust the output power value of attenuated optical signal. Working like a combination of attenuator and power meter, OVA-50 Output Power Control mode enables direct setting of precise optical power level and can automatically stabilize output level without any interference by variations of input power.

➤ Program Mode

User can preprogram frequently-used attenuations to reduce workload.

Address : Perpa Ticaret Merkezi, A Blok No.516 Şişli/İstanbul | Tel : +90 212 3204030 | Fax : +90212 3200255 | e-mail : info@telkolink.com

www.telkolink.com

© 2009 telkolink Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000175 Rev. C



Specifications

Model	OVA-50
Wavelength Range	1260~1650nm
Calibrated Wavelengths	1310/1490/1550/1625nm
Fiber Type	9/125µm Singlemode
Attenuation Range	2.5 - 60dB
Insertion Loss	<2.5dB
Max Input Power	+21dBm
Output Power Range ⁽¹⁾	+18 ~ -55 dBm
Setting Time	<3s
Display Resolution	0.01dB
Attenuation Accuracy	±0.25dB @+25°C (Output power control mode)
Repeatability	±0.25dB @+25°C
Return Loss	≥55dB
Connector	FC/PC (Interchangeable SC,ST)
Power Saving	Auto-off after 5 minutes idle
Backlight	Yes
Power Supply	Li-Ion Battery/AC Adaptor
Battery Life	Continuous operation >30hours
Weight	345g (0.7 lbs)
Dimensions (H × W × T)	177×80×44mm (6.97×3.15×1.73 inch)

Note: (1) Input power level should be at least 3 dB higher than selected output power level;
Input power variations in frequency range <0.5 Hz

* Specifications subject to change without notice

Ordering Information

Standard Configuration:

Instrument, Lithium battery, AC adapter, USB cable, OVA software CD, Soft carrying case, Warranty card, CE certificate, Certificate of Calibration, User's manual.

Address : Perpa Ticaret Merkezi, A Blok No.516 Şişli/İstanbul | Tel : +90 212 3204030 | Fax : +90212 3200255 | e-mail : info@telkolink.com

www.telkolink.com

© 2009 telkolink Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000175 Rev. C