

Overview

PoE Switches are Full gigabit , managed , 16/24-port Gigabit high power (IEEE 802.3at) PoE Switches,

utilizing a compact factor which can be mounted in a 19-inch rack with rack-mounting kits or placed on desktop.

With data and power supported by one unit, the Switches shall reduce cables and eliminate the need for dedicated electrical outlets on the wall,

ceiling or any unreachable place. Auto PoE detection and Plug and play installation makes Gigabit PoE Switch easy to use and


with clear LED indicators to tell the working condition.

Address : Perpa Ticaret Merkezi, A Blok No.516 Şişli/İstanbul | Tel : +90 212 3204030 | Fax : +90212 3200255 | e-mail : info@telkolink.com

www.telkolink.com

© 2009 telcolink Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000175 Rev. C

Quality Link Connections



Hardware Features

	<p>P3018M-16POE-150W</p> <p>16*10/100/1000M PoE ports;; 2* Gigabit SFP ports; IEEE 802.3af/at-compliant; Total Power Consumption:150W.</p>		<p>P3018M-16POE-300W</p> <p>16*10/100/1000M PoE ports;; 2* Gigabit SFP ports; IEEE 802.3af/at-compliant; Total Power Consumption: 300W.</p>
	<p>P3026M-24POE-300W</p> <p>24*10/100/1000M PoE ports;; 2* Gigabit SFP ports; IEEE 802.3af/at-compliant; Total Power Consumption:300W.</p>		<p>P3026M-24POE-450W</p> <p>24*10/100/1000M PoE ports;; 2* Gigabit SFP ports; IEEE 802.3af/at-compliant; Total Power Consumption: 450W.</p>

Address : Perpa Ticaret Merkezi, A Blok No.516 Şişli/İstanbul | Tel : +90 212 3204030 | Fax : +90212 3200255 | e-mail : info@telkolink.com

www.telkolink.com

© 2009 telcolink Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000175 Rev. C

Quality Link Connections



Characteristics

- **P3018M-16POE-150W**: Max Output Power: 150W, supports at most 9* 802.3af-compliant powered devices(power/port: 15.4W) or 4*802.3at-compliant powered devices(power/port:30W);
- **P3018M-16POE-300W**: Max Output Power: 300W, supports at most 16* 802.3af-compliant powered devices(power/port: 15.4W) or 9*802.3at-compliant powered devices(power/port:30W);
- **P3026M-24POE-300W**: Max Output Power: 300W, supports at most 19* 802.3af-compliant powered devices(power/port: 15.4W) or 9*802.3at-compliant powered devices(power/port:30W);
- **P3026M-24POE-450W**: Max Output Power: 450W, supports at most 24* 802.3af-compliant powered devices(power/port: 15.4W) or 14*802.3at-compliant powered devices(power/port:30W);
- Compatible with both IEEE802.3at(30W) and IEEE802.3af(15.4W), can supply power to PDs under these two standards;
- Transmitting electronic power together with data through a single network cable, free of power lines;
- Automatically detect and supply power to IEEE802.3at and IEEE 802.3af compliant powered devices(PDs);
- Advanced SAFC function, only supply power to IEEE 802.3af/at compliant PDs, no worry about damaging other private standard PoE devices or devices without PoE function;
- Support port power supply prioritization, guarantee the continuous power supply of key nodes;
- Up to 100m network cable transmitting distance, support flexible network expansion without power line deployment concerns. Users can freely fix their wireless APs, IP cameras or other end devices on the wall or ceiling;
- Built-in PSE power supply module, plug-and play design, easy to install;

Address : Perpa Ticaret Merkezi, A Blok No.516 Şişli/İstanbul | Tel : +90 212 3204030 | Fax : +90212 3200255 | e-mail : info@telkolink.com

www.telkolink.com

© 2009 telcolink Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000175 Rev. C



- High security performance defending against power surge;
- Support short-circuit protection function, the switch will automatically start short-circuit function and cut off the power supply when there is high-current or other power failures, which can efficiently defend against device damage or network failures caused by line fault or wrong installation;
- Energy-saving green design, support auto-switch to standby mode and auto-detect cable length. It will stay in standby mode and save the power when the port is disconnected , or provide a lower transmission power when the network cable is less than 10m;
- Support simple WEB management, easy to configure the functions of switches.

Address : Perpa Ticaret Merkezi, A Blok No.516 Şişli/İstanbul | Tel : +90 212 3204030 | Fax : +90212 3200255 | e-mail : info@telkolink.com

www.telkolink.com

© 2009 telcolink Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000175 Rev. C

Quality Link Connections



Product Specifications

Items	P3018M-16POE-150W	P3018M-16POE-300W	P3026M-24POE-300W	P3026M-24POE-450W
Fixed Ports	16*10/100/1000M PoE ports	16*10/100/1000M PoE ports	24*10/100/1000M PoE ports	24*10/100/1000M PoE ports
	2 * Gigabit SFP ports	2 * Gigabit SFP ports	2 * Gigabit SFP ports	2 * Gigabit SFP ports
PoE standards	IEEE802.3af/at	IEEE802.3af/at	IEEE802.3af/at	IEEE802.3af/at
Max Output Power(single port)	30W	30W	30W	30W
Total Power Consumption	150W	300W	300W	450W
PoE Pin-out	1/2(+), 3/6(-); Customized 4/5(+),7/8(-)			
Switching Capacity	≥36Gbps		≥52Gbps	
Forwarding Mode	Full wire-speed storage and forwarding			
Forwarding Rate	10M: 14880pps/port			
	100M: 148809pps/port			
	1000M: 1488095pps/port			
Operation Temperature	-20~50°C			
Storage Temperature	-40~70°C			
Operation Humidity	10%~90%(non-condensing)			
Storage Humidity	5%~95%(non-condensing)			
Dimensions	440 (L)×285(W)44.5(H)mm		440 (L)×285(W)44.5(H)mm	
Input Power Supply	AC: 90-264V~ 50-60Hz/150W	AC: 90-264V ~ 50-60Hz/300W	AC: 90-264V ~ 50-60Hz/300W	AC: 90-264V ~ 50-60Hz/450W
Weight	<8Kg		<10Kg	
LED Indicator	Power, Link/Act, PoE Status			
Energy Saving	Comply with “EEE” Energy Efficient Ethernet			

Address : Perpa Ticaret Merkezi, A Blok No.516 Şişli/İstanbul | Tel : +90 212 3204030 | Fax : +90212 3200255 | e-mail : info@telkolink.com

www.telkolink.com

© 2009 telcolink Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000175 Rev. C

Quality Link Connections



Service Characteristics

Items	P3018M-16POE-150W	P3018M-16POE-300W	P3026M-24POE-300W	P3026M-24POE-450W
Standards and Protocols	IEEE 802.3af, Power Over Ethernet			
	IEEE 802.3at, Power Over Ethernet Plus			
	IEEE 802.3u, 100BASE-TX			
	IEEE 802.3ab, 1000 BASE-T			
	IEEE 802.3z, 1000 BASE-X			
	IEEE 802.3ad, Static or Dynamic Link Aggregation			
	IEEE 802.3x, Full-Duplex Flow Control			
	IEEE 802.3az, EEE(Energy Efficient Ethernet)			
	IEEE 802.1q, VLAN			
	IEEE 802.1p, QoS/CoS			
	IEEE 802.1d, STP(Spanning Tree Protocol)			
	IEEE 802.1w, RSTP(Rapid Spanning Tree Protocol)			
	MAC Address Table	Up to 16K MAC addresses		
Support auto-update, two-way learning				
VLAN	Support up to 4096 VLANs			
	Port-based VLANs			
	VLANs based on IEEE 802.1q			
Spanning Tree	Support Spanning Tree Protocol			
	Support Rapid Spanning Tree Protocol(RSTP)			
Link Aggregation	Support 8 aggregation groups, and a maximum of 4 ports in each aggregation group			
Ring Protection	Support Ring Protection, provide real-time detecting, quick alarm, precise localization, smart blocking and auto-recovery			
Port Isolation	Isolation between downlink ports without influence the communication between downlink and uplink ports			
Port Flow Control	Back-pressure traffic control under Half-Duplex mode			

Address : Perpa Ticaret Merkezi, A Blok No.516 Şişli/İstanbul | Tel : +90 212 3204030 | Fax : +90212 3200255 | e-mail : info@telkolink.com

www.telkolink.com

© 2009 telcolink Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000175 Rev. C




	IEEE 802.3x traffic control under Full-Duplex mode
Port Rate Restriction	Port-based ingress or egress rate limiting
Jumbo Frame	Maximum supports 9216 Byte
Multicast Control	Support IGMP Snooping
Storm Suppression	Support the suppression of broadcast storm based on forwarding rate
Security	Port-base MAC address binding
	Security restriction on port-based MAC address quantity
QOS	SP (Strict Priority)
	WFQ (Weighted Fair Queuing)
	WRR (Weighted Round Robin)
	802.1p(Port Queuing Priority)
	Differentiated Service Code Point(DSCP Priority)
PoE ouput priority Management	Supported
Physic Medium	10/100Base-TX: UTP category 3/4/5 cables(Maximum 100m)
	1000Base-T: UTP Category 5 cable(Maximum 100m)
	1000Base-SX: fiber with 850nm wavelength, supports a max transmission distance of 550m
	1000Base-LX: fiber with 1310nm / 1550nm wavelength, supports a max transmission distance of 80km
Network Cable Deployment	Support Auto-MDIX function, automatically identify straight forward cable and cross-over cable
Negotiation Pattern	Support port auto-negotiation function(automatically negotiate transmission rate and Duplex modes)
Maintenance	Detect the connectivity of network cables
	Uploading or downloading of the configuration data
	Uploading of upgrade patch
	WEB-based reset to factory defaults
	Support port short-circuit reset to factory defaults
Management	Support WEB-based management

Address : Perpa Ticaret Merkezi, A Blok No.516 Şişli/İstanbul | Tel : +90 212 3204030 | Fax : +90212 3200255 | e-mail : info@telkolink.com

www.telkolink.com

© 2009 telcolink Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000175 Rev. C



Ordering Information

Model Number	Detailed information
P3018M-16POE-150W	16*10/100/1000M PoE ports+2* Gigabit SFP ports;IEEE 802.3af/at-compliant;Total Output Power:150W;
P3018M-16POE-300W	16*10/100/1000M PoE ports+2* Gigabit SFP ports;IEEE 802.3af/at-compliant;Total Output Power: 300W;
P3026M-24POE-300W	24*10/100/1000M PoE ports+2* Gigabit SFP ports;IEEE 802.3af/at-compliant;Total Output Power:300W;
P3026M-24POE-450W	24*10/100/1000M PoE ports+2* Gigabit SFP ports;IEEE 802.3af/at-compliant;Total Output Power: 450W;

Address : Perpa Ticaret Merkezi, A Blok No.516 Şişli/İstanbul | Tel : +90 212 3204030 | Fax : +90212 3200255 | e-mail : info@telkolink.com

www.telkolink.com

© 2009 telcolink inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000175 Rev. C

Quality Link Connections

