

RG 216/U

KOD NO : 9730 0200
İLGİLİ STANDART : MIL-C-17

KABLO YAPISI

1 - İÇ İLETKEN (mm) : 7x0,40 mm kalaylı bakır
2 - YALITKAN ÇAPI (mm) : PE 7,25 mm
3 - 1.EKRAN : Kırmızı bakır örgü
4 - 2.EKRAN : Kırmızı bakır örgü
5 - DIŞ KILIF ÇAPI (mm) : 10,80 mm siyah PVC

TEKNİK BİLGİLER

1 - EMPEDANS (ohm) : 75 ±3
2 - KAPASİTE (pF/m) : 67
3 - YAYILMA HIZI (v /c) : 0,66
4 - ÇALIŞMA SICAKLIĞI : -40 +70°C
5 - TEST GERİLİMİ : 5,0 KV
6 - ZAYIFLAMA (dB / 100m) :

100 MHz
6,5

200 MHz
9,6

500 MHz
16

800 MHz
21

KULLANIM ALANI

Düşük zayıflama istenen anten sistemleri, enstrüman ve cihazlarda bağlantı kablosu olarak kullanılır.

Address : Perpa Ticaret Merkezi, A Blok No.516 Şişli/İstanbul | Tel : +90 212 3204030 | Fax : +90212 3200255 | e-mail : info@telkolink.com

www.telkolink.com

© 2009 telcolink Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000175 Rev. C

Haberleşme sistemlerinde yüksek performansı yakalayın

