

RP-2703

10Base-T to 10Base-2 Media Converter



RP-2703 is a media converter that transmits signals between Ethernet 10Base-T UTP medium and Thin Ethernet Coaxial medium. Collision data are transmitted to ensure 100% collision detection in the combination of network segments or devices. RP-2703 is an ideal solution that provides connection from 10Base-T to Thin-Net backbone, where BNC port is not available on the existing 10Base-T concentrator. It provides a plug-and-play solution at very low cost.

In a match-box similar size, RP-2703 can be easily installed in the environment with limited space. Four diagnostic LED indicators provide clear and quick diagnosis if any network problem is encountered. RP-2703 comes with an external AC power adapter.

Feature

- 10M Ethernet 10Base-T/2converter
- RJ-45 connector for UTP interface
- UTP CAT 3 or 5 cable up to 100-meter

Specification

Standards	• IEEE802.3 10Base-T/10Base-2
Connectors	• 1* UTP RJ-45 Jacks, • 1* BNC Connector
Cable	• UTP: Cat.3 UTP cable • Coaxial: RG-58A/U thin cable
Maximum wire Length	• UTP: 100m • Coaxial: 185m per segment
Data Transfer Rate	• 10Mbps
LED Indicator	• BNC ACT, Power, TP Link/Activity, Collision
Power Supply	• External Power Adapter DC5V1A
Environment	• Operating temperature : 0°C to 50°C • Operating Humidity:5% to 90% (Non-Condensing)
Dimension	• 26.2 * 70.3 * 94 mm
Certification	• FCC, CE

Ordering information

RP-2703 10Base-T to 10Base-2 Media Converter

Address : Perpa Ticaret Merkezi, A Blok No.516 Şişli/İstanbul | Tel : +90 212 3204030 | Fax : +90212 3200255 | e-mail : info@telkolink.com

www.telkolink.com

© 2009 telcolink Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000175 Rev. C

