

RP-ISF082G

8-Port 10/100TX + 2-P 1000T/SFP Industrial Ethernet Switch



The RP-ISF082G is a 8-port 10/100TX+ 2-P 1000T/SFP Industrial Switch, it is a cost-effective solution and meets the high reliability requirements demanded by industrial applications, such as factory assembly line, automation, transportation and heavy Industrial factory.

The switch comes with wide range of voltages (12 to 48V DC) power supply source, which secure equipment against unregulated voltage and make systems safer and more reliable.

The switch with IP-30 standard compact metal case allows either DIN rail or wall mounting for efficient use of cabinet space.

Feature

- RJ-45 port support Auto MDI/MDI-X Function
- SFP(Mini-GBIC) supports 100/1000 Dual Mode
- Store-and-Forward Switching Architecture
- Back-plane (Switching Fabric): 5.6Gbps
- 1Mbits Packet Buffer
- 8K MAC Address Table
- Support Wide Operating Temperature
- Power Polarity Reverse Protect
- Overload Current Re-settable Fuse Present
- IP-30 Protection
- DIN Rail and Wall Mount Design
- Provides EFT protection 3000 VDC for power line
- Supports 6000 VDC Ethernet ESD protection

Specification

Standards	<ul style="list-style-type: none"> • IEEE 802.3 10Base-T Ethernet • IEEE 802.3u 100Base-TX Fast Ethernet • IEEE 802.3ab 1000Base-T • IEEE802.3z Gigabit fiber • IEEE 802.3x Flow Control and Back Pressure
Switch Architecture	<ul style="list-style-type: none"> • Back-plane (Switching Fabric): 5.6Gbps • Packet throughput ability (Full-Duplex): 8.3pps @64bytes
Transfer Rate	<ul style="list-style-type: none"> • 14,880pps for Ethernet port • 148,800pps for Fast Ethernet port • 1,488,000pps for Gigabit Fiber Ethernet port
Buffer Memory	<ul style="list-style-type: none"> • 1Mbits
Mac Address	<ul style="list-style-type: none"> • 8K MAC
Interface	<ul style="list-style-type: none"> • 10/100TX: 8 x RJ-45 • 10/100/1000T/ SFP Combo: 2 x RJ-45 + 2 x 100/1000 SFP sockets
Network Cable	<ul style="list-style-type: none"> • 10Base-T: 2-pair UTP/STP Cat. 3, 4, 5 cable EIA/TIA-568 100-ohm (100m) • 100Base-TX: 2-pair UTP/STP Cat. 5/ 5E cable EIA/TIA-568 100-ohm (100m)
Optical Cable	<ul style="list-style-type: none"> • Multi-mode: 50/125um~62.5/125um • Single-mode: 9/125um
Protocol	<ul style="list-style-type: none"> • CSMA/CD
LED Indicators	<ul style="list-style-type: none"> • Per unit: Power 1 (Green), Power 2 (Green), Fault (Red) • 8 10/100TX : Link/Activity (Green), Full duplex/Collision (Yellow) • Giga port: Link/Activity (Green)
Reserve polarity protection	<ul style="list-style-type: none"> • Present
Overload current protection	<ul style="list-style-type: none"> • Present
Case	<ul style="list-style-type: none"> • Metal case. IP-30
Installation	<ul style="list-style-type: none"> • DIN Rail and Wall Mount Design
Power Consumption	<ul style="list-style-type: none"> • 6.76W
Power Supply	<ul style="list-style-type: none"> • DC 12~48V, Redundant power with polarity reverse protect function and removable terminal block
Environment	<ul style="list-style-type: none"> • Operating temperature : Standard: -10°C ~60°C ; • Operating Humidity: 5% to 95% (Non-Condensing)
Dimension	<ul style="list-style-type: none"> • 72 * 105 * 152mm
Certification	<ul style="list-style-type: none"> • FCC, CE

Ordering information

RP-ISF082G 8-Port 10/100TX + 2 1000T/ SFP Industrial Ethernet Switch

Address : Perpa Ticaret Merkezi, A Blok No.516 Şişli/İstanbul | Tel : +90 212 3204030 | Fax : +90212 3200255 | e-mail : info@telkolink.com

www.telkolink.com

© 2009 telcolink Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000175 Rev. C

