

RP-ISG401F

5-P slim type Gigabit Industrial Switch

RP-ISG401F provides 5 Gigabit Ethernet ports which is designed for supporting standard industrial applications without complex setup to make the network truly plug-and-play, it can be used in connecting several Ethernet devices like Ethernet I/O, IP-Camera or other Ethernet

switches. In addition, it provides wide power input voltage range +12 ~ + 58Vdc for application flexibility which secure equipment against unregulated voltage and make systems safer and more reliable.

With the 5 10/100/1000Mbps Gigabit Ethernet ports RP-ISG401F provides non-blocking switch fabric and wire-speed throughput as high as 10Gbps, RP-ISG401F performs wire-speed packets transfer without risk of packet loss.

With compact IP-30 standard metal case protection allows either DIN rail or wall mounting for efficient use of cabinet space.



Feature

- RJ-45 port support Auto MDI/MDI-X Function
- Store-and-Forward Switching Architecture
- Back-plane (Switching Fabric): 10Gbps
- IEEE 802.3x flow control & back-pressure
- 9K Jumbo frames
- 2K MAC forwarding addresses
- L2 wire-speed switching engine
- Queues per port: 4
- Support 802.1p & TOS/DS QoS
- Support Multicast/Broadcast/Flooding Storm Control
- Wide-range Redundant Power design 12~58 VDC, removable terminal block for two power input
- Reverse power protection
- Hardware DIP-switch to enable/disable warning function
- IP-30 metal case protection
- DIN rail and wall mount design

Specification

Standards	<ul style="list-style-type: none"> • IEEE 802.3 10Base-T Ethernet • IEEE 802.3u 100Base-TX Fast Ethernet • IEEE 802.3ab 1000Base-T Gigabit Ethernet • IEEE 802.3z 1000Base-X Gigabit Ethernet • IEEE802.3x Flow Control and Back Pressure
Switch Architecture	<ul style="list-style-type: none"> • Back-plane (Switching Fabric): 10Gbps
Transfer Rate	<ul style="list-style-type: none"> • 14,880pps for Ethernet port • 148,800pps for Fast Ethernet port • 1,488,000pps for Gigabit Fiber Ethernet port
Data Processing	<ul style="list-style-type: none"> • Store and Forward
Flow Control	<ul style="list-style-type: none"> • IEEE 802.3x Flow Control and Back Pressure
Jumbo Frame	<ul style="list-style-type: none"> • 9K Bytes
MAC Table Size	<ul style="list-style-type: none"> • 2K
Network Connector	<ul style="list-style-type: none"> • RJ-45 Port: 10/100/1000BaseT(X) auto negotiation, Auto MDI/MDI-X function, Full/Half duplex • SFP Port: 100/1000BaseSFP slot
Network Cable	<ul style="list-style-type: none"> • UTP/STP above Cat.5e Cable, EIA/TIA-568 100-ohm (100m)
Protocol	<ul style="list-style-type: none"> • CSMA/CD
Flow control	<ul style="list-style-type: none"> • IEEE 802.3x (Full Duplex) and Back-Pressure (Half Duplex)
QoS	<ul style="list-style-type: none"> • IEEE 802.1p
Number of queues	<ul style="list-style-type: none"> • 4
Traffic Shaper	<ul style="list-style-type: none"> • Port-based Port shaping
Storm Control	<ul style="list-style-type: none"> • Multicast/Broadcast/Flooding Storm Control per system basis enable/disable
Dip switch	<ul style="list-style-type: none"> • Dip 1: On/Off - Power alarm • Dip 2: On/Off - Broadcast storm rate limit • Dip 3~6: Not used
LED indicators	<ul style="list-style-type: none"> • P1(Green), P2(Green), Alarm (Red) • RJ-45: Link/Act (Green): Ethernet link up Link/Act (Yellow): On- 1000Mbps ; Off-10Mbps or 100 Mbps • SFP: Link/Act (Green): Ethernet link up Link/Act (Yellow): On-1000Mbps ; Off-100 Mbps
Power Supply	<ul style="list-style-type: none"> • Redundant Input Terminals 12-58 VDC
Operating Temperature	<ul style="list-style-type: none"> • -40 to +75°C (cold startup at -40°C)
Storage Temperature	<ul style="list-style-type: none"> • -40 to +85 °C
Operating Humidity	<ul style="list-style-type: none"> • 5% to 95% (Non-condensing)
Case	<ul style="list-style-type: none"> • Rugged Metal, IP30 Protection
Dimension	<ul style="list-style-type: none"> • 112.2(H) x 29.1(W) x 89.4(D) (without DIN rail clip)
Installation mounting	<ul style="list-style-type: none"> • DIN Rail mounting and Wall Mounting
Certification	<ul style="list-style-type: none"> • CE/FCC
EMI	<ul style="list-style-type: none"> • FCC Part 15, CISPR 22 (EN55022) Class A IEC61000-4-2, -3, -4, -5, -6 (Level 3)

Ordering information

RP-ISG401F 4-P slim type Gigabit +1-SFP(100/1G) slot Industrial Switch

Address : Perpa Ticaret Merkezi, A Blok No.295 Sisli/Istanbul | Tel : +90 212 3204030 | Fax : +90212 3200255 | e-mail : info@telcolink.com

www.telcolink.com

© 2009 telcolink Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000175 Rev. C

Quality Link Connections

