

RP-1200ES+

2-Port 10GBase-SR/LR SFP+ PCI Express Adapter



RP-1200ES+ is a PCIe bus 2-Port 10GBase-SR/LR SFP+ fiber NIC that fully complies with IEEE 802.3ae standards. It provides up to 20Gbps full-duplex bandwidth capacity to support high-end servers. It is suitable for Data Center, SMB and Cloud computing applications. Two LED indicators (LINK and ACT) on the bracket will help to oversee the board link and activities status.

Feature

- High bandwidth 10Gbps Network Speed
- Supports IEEE 802.3x Full-Duplex Flow Control
- Comply with PCIe 2.0 Interface
- Supports Jumbo Frame up to 10Kbytes
- Supports GpXe
- Supports IEEE 802.3ad Link Aggregation (LACP)
- Supports on-board screening of VLAN tagged Ethernet frames

Address : Perpa Ticaret Merkezi, A Blok No.516 Şişli/İstanbul | Tel : +90 212 3204030 | Fax : +90212 3200255 | e-mail : info@telkolink.com

www.telkolink.com

© 2009 telcolink Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000175 Rev. C



Specification

Standards	<ul style="list-style-type: none"> • IEEE 802.3ae 10GBase-SR/LR • IEEE 802.3x Full-Duplex with NWay Flow Control • IEEE 802.3ad LACP • IEEE 802.1Q VLANs • IEEE 802.1p priority
Connector	<ul style="list-style-type: none"> • SFP+: 10Gbps
Cable	<ul style="list-style-type: none"> • Fiber (M-M): 50/125,62.5/125m • Fiber (S-M): 9/125m
Data Transfer Rate	<ul style="list-style-type: none"> • 10Gbps:14,880,000 pps
LED Indicators	<ul style="list-style-type: none"> • LINK (Green) • ACT (Amber)
Bus Slot	<ul style="list-style-type: none"> • PCI Express 2.0 compliant
Software Support	<ul style="list-style-type: none"> • Windows server 2003 • Windows server 2008 • RHEL v5.0 • XenServer 5.6.0 • VMware ESXi 4.0
PCIe Input	<ul style="list-style-type: none"> • 12VDC, 3.3VDC
Environment	<ul style="list-style-type: none"> • Operating temperature : 0°C to 40°C • Operating Humidity:5% to 90% (Non-Condensing)
Dimension	<ul style="list-style-type: none"> • 168 * 64mm
Certification	<ul style="list-style-type: none"> • FCC, CE

Ordering information

RP-1200ES+ 2-Port 10GBase-SR/LR SFP+ PCI Express Adapter

Address : Perpa Ticaret Merkezi, A Blok No.516 Şişli/İstanbul | Tel : +90 212 3204030 | Fax : +90212 3200255 | e-mail : info@telkolink.com

www.telkolink.com

© 2009 telcolink Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000175 Rev. C

