

CCTV Test Cihazı Multimetreli



3.5 inch CCTV Tester M-CST-SR5 with Multimeter

The CCTV Tester M-CST-SR5 offers technicians a wide range of features to simplify CCTV camera installations. Power, focus and aim your cameras locally without a trip back to the control room. The unit's bright screen and easy to use menu are ideal for outdoor use. A durable rubberized skin helps protect the unit from general wear. A lanyard and a hand strap are included to ease installs in locations.

This device allows the installer to control PTZ cameras that accept data over RS232, RS422 simplex or RS485 ports. The Address Search feature can be used to run a search and determine a PTZ unit's address. The UTP cable test feature checks for connectivity across all 8 wires and also displays the pin-to-pin connections of the RJ45 connectors.

The unit includes a rechargeable Lithium Ion Polymer battery that charges for 4 hours and can last up to 12 hours in the field. An auxiliary 12VDC, 1A power supply can be used to locally power and adjust cameras in the field or on a test bench. The RS485 data capture feature displays the code output of serial control devices.

And it Supports more than twenty PTZ protocols. For example, Pelco-P, Pelco-D, Samsung, Panasonic, CBC, Bosch, TeleEye, Vicon, Sanyo-SSP etc.

Specification:

Signal System	NTSC / PAL (Auto-Selecting)
---------------	-----------------------------

Display	3.5 inch TFT-LCD
Resolution	960 x 240 (H x V)
LCD adjust	Adjustable brightness, contrast, color of LCD
Video Input / Output	1 channel BNC input & 1 channel BNC looped output
Video Level Test	Video signals measured in IRE or mV
Power Adapter	5V DC, 2A input supply
Power output	12V DC, 1A supply
Audio input	1 channel Audio input
Communication	RS232, RS422 simplex and RS485
Baud Rate	150, 300, 600, 1200, 2400, 4800, 9600, 19200bps
Power Saving Features	Sleep mode, Battery level indicator
PTZ Address Scanning	Scan for local PTZ address over data cables
Rechargeable Battery	4 hours charge, work for 12 hours
Battery	1 pcs Lithium Ion Polymer Battery; 3.7V DC, 3000mAh
Video Display	Displays video signal from analog input
Video Signal Generation	Color bar generator for monitor testing
UTP Cable Test	Checks connections of UTP cables
PTZ Protocol	Compatible with more than 20 protocols such as PELCO-D/P, Samsung, Panasonic, TeleEye etc.
PTZ data Capture	Reads and displays commands sent from controllers
MultiMeter	Voltage, current, resistance and capacitance measuring, continuity testing, diode testing.
Dimension	185mm x 110mm x 40mm
Gross Weight	980g



www.gym-tech.net

| Tel : +90 212 3204030
| Fax : +90212 3200255
| e-mail : info@telkolink.com
| Address : Perpa Ticaret Merkezi, A Blok No.516 Şişli/İstanbul

|Haberleşme & Telekom & Network Ürünleri



www.telkolink.com