



Type	Construction				Electric Properties				
	Conduct	Insulation Dia.	Outer Conductor	Jacket	Z( $\Omega$ ).	V	Capacitance (pF/m)	Attenuation	
								MHz	dB/100m
SYV-75-2-1	1/0.34 bare copper	2.05mm LDPE	braiding coverage $\geq 92\%$ Single	3.3 $\pm$ 0.1 mm FRPVC	75 $\pm$ 3	66%	$\leq 72$	1	2.1
								2	3.0
								4	4.3
								10	6.8
								30	11.0
78	18.5								
200	29.0								
SYV-75-2-2	1/0.34 bare copper	2.05mm LDPE	braiding coverage $\geq 92\%$ Double	3.9 $\pm$ 0.1 mm FRPVC	75 $\pm$ 3	66%	$\leq 72$	1	2.1
								2	3.0
								4	4.3
								10	6.8
								30	11.0
78	18.5								
200	29.0								
SYV-75-2-1	1/0.32 bare copper	9mm LDPE	braiding coverage $\geq 80\%$ Single	3.4 $\pm$ 0.1 mm PVC	75 $\pm$ 3	66%	$\leq 72$	30	16.0
SYV-75-3-1	1/0.5 bare copper	3.0mm LDPE	braiding coverage $\geq 92\%$ Single	5.0 $\pm$ 0.2 mm FRPVC	75 $\pm$ 3	66%	$\leq 72$	1	1.6
								2	2.2
								4	3.0
								10	5.3
								30	9.2
78	16.4								
200	25.0								
SYV-75-3-2	1/0.5 bare copper	3.0mm LDPE	braiding coverage $\geq 92\%$ Double	5.5 $\pm$ 0.2mm FRPVC	75 $\pm$ 3	66%	$\leq 72$	1	1.6
								2	2.2
								4	3.0
								10	5.3
								30	9.2
78	16.4								
200	25.0								
SYV-75-3-1	7/0.17 Bare copper	3.0mm LDPE	Braiding Coverage $\geq 92\%$ Single	5.0 $\pm$ 0.2 mm FRPVC	75 $\pm$ 3	66%	$\leq 72$	1	1.6
								2	2.2
								4	3.0
								10	5.3
								30	9.2

Type	Contraction				Electric Properties				
	Conductor	Insulation & Dia.	Outer conductor	Jacket	Z( $\Omega$ ).	V	C (pF/m)	Attenuation	
								MHz	dB/100m
								78	16.4
								200	25.0
SYV-75-3-2	7/0.17 Bare Copper	3.0mm LDPE	Braiding Coverage $\geq 92\%$ Double	5.5 $\pm$ 0.2 mm FRPVC	75 $\pm$ 3	66%	$\leq 72$	1 2 4 10 30 78 200	1.6 2.2 3.0 5.3 9.2 16.4 25.0
SYV-75-4-1	1/0.61 Bare Copper	3.8mm LDPE	Braiding Coverage $\geq 92\%$ Single	6.0 $\pm$ 0.2 mm FRPVC	75 $\pm$ 3	66%	67 $\pm$ 4	1 4 17 70 78 210	1.1 2.4 5.0 9.9 10.5 18.0
SYV-75-4-2	1/0.61 Bare Copper	3.8mm LDPE	Braiding Coverage $\geq 92\%$ Double	7.5 $\pm$ 0.3 mm FRPVC	75 $\pm$ 3	66%	67 $\pm$ 4	1 4 17 70 78 210	1.1 2.4 5.0 9.9 10.5 18.0
SYV-75-4-1	7/0.21 Bare Copper	3.8mm LDPE	Braiding Coverage $\geq 92\%$ Single	6.0 $\pm$ 0.3 mm FRPVC	75 $\pm$ 3	66%	67 $\pm$ 4	1 4 17 70 78 210	1.1 2.4 5.0 9.9 10.5 18.0
SYV-75-5-1	1/0.74 Bare Copper	4.6mm LDPE	Braiding Coverage $\geq 92\%$ Single	7.0 $\pm$ 0.2 mm FRPVC	75 $\pm$ 3	66%	67 $\pm$ 4	1 4 17 70	1.0 2.0 4.3 8.8
SYV-75-5-2	1/0.74 Bare Copper	4.6mm LDPE	Braiding Coverage 编织密度 $\geq 92\%$ Double 双层	8.15 $\pm$ 0.3 mm FRPVC 稀	75 $\pm$ 3	66%	67 $\pm$ 4	1 4 17 70	1.0 2.0 4.3 8.8

Address : Perpa Ticaret Merkezi, A Blok No.516 Şişli/İstanbul | Tel : +90 212 3204030 | Fax : +90212 3200255 | e-mail : info@telkolink.com

[www.telkolink.com](http://www.telkolink.com)

© 2009 telcolink Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000175 Rev. C

Haberleşme sistemlerinde **yüksek performans**ı yakalayın

