

9/125 (OS1/OS2) Optical Fibre Pigtails

Product Datasheet

V.3.0

Description


singlemode pigtails are used in telecom, datacom networks and also used for high speed metropolitan and access network. The singlemode pigtail buffer conforms to IEC, EIA TIA and Telecordia standards. The singlemode pigtails are terminated with standard connector which gives optimum optical performance.

Features / Benefits

- ▶ SC, LC, ST, FC and E2000 connectors
- ▶ PC and APC connectors
- ▶ Low smoke zero halogen (LSZH) buffer
- ▶ 900 μ m tight buffer or easy strip
- ▶ OS1/OS2 fibre conforms to ITU-G652.D, TIA/EIA 492 CAAA
- ▶ OS1/OS2 bend insensitive conforms to ITU-G657.A
- ▶ Different connector performance range for specific application
- ▶ Available in standard white colour buffer and also in standard 12 colours as per IEC 60304
- ▶ Available in standard and blister packing

Applications

- ▶ Telecom and datacom application
- ▶ Patch panels, wall boxes, ODFs and splice cassettes
- ▶ Easy strip pigtails for on site installation
- ▶ Supports high speed multi channel video, data and voice services in metropolitan and access networks
- ▶ ATM, SONET and WDM



Connector Specification

OPTICAL PERFORMANCE	SINGLEMODE	CONFORMANCE
Insertion loss (Typ)	0.25 dB	IEC 61300-3-4
Ave/Master*	0.18 dB	IEC 61300-3-4
Ave/Random*	0.18 dB	IEC 61300-3-34
Return Loss	50/60 dB	IEC 61300-3-6

Cable Specification

CHARACTERISTICS	UNITS	SIMPLEX
Crush	N/100mm	500
Operating Temperature	°C	-20 to 60
Nominal buffer Diameter	μ m	900+50
Max Tensile Load	N	6

Fibre Specification

CHARACTERISTICS	
Attenuation (dB)	0.38 @ 1310nm / 0.25 @ 1550nm
Chromatic Dispersion (ps/nm x km)	3.0 @ 1310nm / 18.0 @ 1550nm
Polarization Mode Dispersion (ps/ \sqrt{km})	\leq 0.2

İletişim Bilgilerimiz

Satış	: yusuf@telkolink.com
Teknik Destek	: sait@telkolink.com
Tel	: 0(212) 320 4030 & 0(212) 320 0255
Mobile	: 0(554) 739 5700 & 0(533) 426 6695
Adres	: Perpa Ticaret Merkezi A Blok K.6 No:516 Okmeydanı Şişli İstanbul

