

# OTS-20/30

## Multifunctional Optical Talk Set

- ◆ Full duplex multiparty call on single fiber
- ◆ Combines laser source and power meter
- ◆ High-quality voice signal
- ◆ Optional nondestructive Clip-on Coupler:
- ◆ Direct online communication
- ◆ Large internal memory: 4000 records
- ◆ PC software for data download and reporting
- ◆ 10 hours continuous operation/Auto off
- ◆ Handheld, damp-dust-shock proof
- ◆ CE FCC FDA certificates



OTS-20/30 Multifunction Optical Talk Set enables clear and long distance telephony on single optical fiber. Featuring integrated laser source and optical power meter for loss test, OTS-20/30 is a reliable toolset for tough environments.

### Specifications

Model	OTS-20		OTS-30	
	A	B	C	D
Display	LED		LCD	
<b>Talk Set Module</b>				
Wavelength (±20nm)	1310	1550	1310	1550
Dynamic Range	40dB		45dB	
Effective Range (Km)	110	160	130	180
Emitter Type	FP-LD			
Spectrum Width	≤5nm			
<b>Laser Source Module</b>				
Wavelength (±20nm)	1310	1550	1310	1550
Output Power (dBm)	≥-5		≥-1	
Modulation Frequencies	270, 1K, 2K Hz			
Stability	±0.05 dB/15min; ±0.15dB/8hr			

Address : Perpa Ticaret Merkezi, A Blok No.516 Şişli/İstanbul | Tel : +90 212 3204030 | Fax : +90212 3200255 | e-mail : info@telkolink.com

[www.telkolink.com](http://www.telkolink.com)

© 2009 telcolink Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000175 Rev. C



Power Meter Module		
Detector Type	NA	InGaAs
Measurement Range <sup>(1)</sup>		-70 ~ +10dBm
Calibrated Wavelength		850,1300,1310,1550nm
Accuracy		±0.25dB (5%) @25°C&-10dBm (±0.5dB@850nm)
Data Storage		4000 records
Connectivity		RS232
General Specifications		
Connector	FC (Interchangeable SC, ST)	
Power Supply	NiMH Battery (1600mA/h) / AC Adapter	
Battery Life	10 hrs continuous operation/16 hrs standby	
Operating Temp.	0°C to 50°C	
Storage Temp.	-20°C to 70°C	
Relative Humidity	0 to 95%(non-condensing)	
Weight	600g (1.3 lbs)	
Dimensions (H×W×T)	196×100×44mm (7.7×3.9×1.7 inch)	

**Note:** (1) For 850nm, the lower limit of measurement range is -60 dBm.

\* Specifications subject to change without notice

## Ordering Information

\* Optical Talk Set is purchased in pair. Two units are required for communication.

Standard Package Includes:

Instrument, NiMH battery, Headset, AC adapter, Rubber boot, Toolkit for soft bag, OTS data analysis software CD (for OTS-30), Data transfer cable (RS232, for OTS-30), Warranty card, CE /FCC certificate, Certificate of calibration, User manual.

## Optional Parts

Part Description	Part Number (P/N)	Part Description	Part Number (P/N)
3M Optical patch cord	AC-FJC-03-FC/FC	Fiber Connector Cleaner	AC-CLN-TAPE
50M Optical patch cord	AC-FJC-50-FC/FC	Connector Clean Stick	AC-CLN-STK
SC connector for LS	AC-CONN-SC-L	Ceramic core for LS	AC-FRL-C
ST connector for LS	AC-CONN-ST-L	Multi-Party Cable	AC-CABL-Multi
SC connector for PM	AC-CONN-SC-P-300	Compact carrying soft bag	AC-PB-20
ST connector for PM	AC-CONN-ST-P-300	Toolkit for luxury package	AC-PB-40

Address : Perpa Ticaret Merkezi, A Blok No.516 Şişli/İstanbul | Tel : +90 212 3204030 | Fax : +90212 3200255 | e-mail : info@telkolink.com

[www.telkolink.com](http://www.telkolink.com)

© 2009 telcolink Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000175 Rev. C